

UK GARDEN BUILDINGS (RUGELEY) LIMITED

Unit N, Beacon Business Park, Weston Road,
Stafford, Staffordshire, ST18 0WL

Telephone: 01889 582000

Website: www.ukgardenbuildings.co.uk Email: sales@ukgardenbuildings.co.uk

Composite Garden Room Information

All our composite buildings are manufactured using the highest quality Ultrashield composite.

Composite garden rooms are becoming exceedingly popular across the world due to its authentic timber look, low maintenance, and its ability not to rot, split or suffer fungal decay.

To ensure your composite garden room retains its original beauty you will need to be aware of the following:

Mineral Deposits

Mineral deposits appear when regular cleaning is not conducted. The deposits appear because of rain mixing with runoff from roofs, fences, trees, hedges etc. When evaporated from the composite it creates a haze on the surface that can be washed away if seen within a certain period. If over time this haze is not cleaned, it can build up and create layers that are more difficult to clean. To remove mineral deposits, you can use a 50/50 solution of water and vinegar, spray the solution on the the affected area, leave for five minutes and use a non-metal scrub brush in the direction of the grain to remove the deposits, finish by rinsing with water and drying the area with a towel to see the results. It may take multiple times scrubbing the boards to get the mineral deposits off the surface.

Mould and Mildew

Mould and mildew occur periodically in everyday environments. Therefore, surface mould and mildew can appear on the composite if decaying organic material such as, but not limited to, wood, leaf decay, and pollen are present along with elevated temperatures, air, and water. There is no way to eliminate mould and mildew, therefore, you can only minimise the occurrence by removing the decaying organic materials as quickly as possible. If mould and mildew are present, use warm soapy water and a soft non-metal scrub brush to clean.

Irregular Heat Sources/Fire

Composite has the tendency to retain heat whenever presented directly or indirectly to it. Irregular heat sources, such as, but not limited to, fire pits, chimineas, barbecues, patio heaters etc may damage the surface of the composite. Precautions should be taken from irregular heat sources to ensure no damage occurs.

Masonry Construction

During masonry construction the composite should be covered with a tarpaulin or construction grade plastic film. Mineral deposits, left over from construction, can mix with water, and evaporate leaving deposits behind which create a white/haze on the surface. These are exceedingly difficult to remove and will require regular maintenance to maintain the original look.

Chemicals, Solvents and Paints

No chemicals, solvents or paints should be used on the composite products. Please also take care when using weed killers around the base of the building avoiding contact with the composite.

N.B. Pressure washers should not be used on Composite Garden Rooms, the psi pressure can damage the composite and the membrane between the composite and internal walls leading to water ingress. Should a pressure washer be used the building guarantees will be void.