

UK GARDEN BUILDINGS (RUGELEY) LIMITED

Unit N, Beacon Business Park, Weston Road,
Stafford, Staffordshire, ST18 0WL

Telephone: 01889 582000

Website: www.ukgardenbuildings.co.uk Email: sales@ukgardenbuildings.co.uk

Tanalised Building Information and Maintenance Guide

Our tanalised timber is treated by Treeway Fencing Ltd for use class 3.1 and 3.2.

All our tanalised buildings have been treated with TANALITH wood preservative under controlled conditions in a vacuum pressure timber impregnation plant.

TANALITH is a water-based wood preservative that contains copper and proven organic biocides. When impregnated into the timber the preservative components bond with the wood structure and cannot easily be removed.

TANALITH pressure treated timber has a long-term protection against fungal and insect attack, including termites, for both in and out of ground contact, interior and exterior applications when treated to the correct usage specification.

TANALITH pressure treated timber has an initial natural green colourisation. Upon external exposure, the green colour slowly weathers to a warm, honey brown and in the long term becomes a silver grey. The weathering process does not indicate any loss of preservative protection.

Due to the thickness and application of the **timber?** on the building, it is deemed appropriate to treat the building timber with a brush-on water repellent.

We offer a fifteen-year guarantee on all our tanalised buildings providing you have regularly treated the building with a superior quality preservative.

Timber Eco Shield is recommended by UK Garden Buildings to prolong the life and appearance of your tanalised building whilst giving a water-proof coating, we offer the colour Pale Green for our tanalised buildings which can be purchased with your building.

Timber Eco Shield is an advanced water-based micro-porous timber treatment using nanotechnology. It creates a long-lasting waterproof wood coating that is friendly to its environment. It is child, pet, and plant friendly, low odour with low VOC's.

Suitable for all types of wood, rough or planed timber and is dry in thirty minutes (perfect for unpredictable British weather).

Timber Eco Shield application tips – for the first treatment, two coats of Timber Eco Shield are recommended and will give a traditional matt finish. It can be used on all exposed timber and for ultimate performance it is advised a preservative pre-treatment has been used, which all our tanalised buildings are supplied with.

If you would like more information on the amount needed to treat your building, please use the coverage calculator on Protek's website: www.protekwoodstain.co.uk.